



Shell Helix *Ultra Professional AF-L 0W-30*

Fully Synthetic Motor Oil - Tailored to meet engine manufacturer special requirements

Designed to meet the demanding requirements of particular high-performance engines from Ford and those requiring ACEA C2

Proud Drivers Choose Shell Helix

Main Applications

- Shell Helix Ultra Professional AF-L for diesel engines is approved against the technically challenging in-house Ford engine oil specification WSS-M2C950-A. Also suitable where ACEA C2 is required.

Specifications, Approvals & Recommendations

- ACEA C2
- Ford WSS M2C-950A
- To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at: <http://lubematch.shell.com>
- Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical help desks.

Typical Physical Characteristics

Properties			Method	Shell Helix Ultra Professional AF-L 0W-30
Kinematic Viscosity	@100°C	cSt	ASTM D445	9.40
Kinematic Viscosity	@40°C	cSt	ASTM D445	44.20
Viscosity Index			ASTM D2270	204
Density	@15°C	Kg/m ³	ASTM D4052	843.0
Flash Point		°C	ASTM D92	206
Pour Point		°C	ASTM D97	-43

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from www.epc.shell.com

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.